

# Playset

## PROJECT PLAN

**YellaWood**<sup>®</sup>  
Pressure Treated Pine



## Build a durable and fun playset for your children's backyard adventures.

This playset calls for a slide and 2 swings and features a sturdy frame, 2 ladders, and a crow's nest peer-out point with a raised platform.

It is an outdoor fixture that will last and have the whole family spending more time outside.

You'll start with the construction of the A-frame supports, then move on to

assembling the main skeleton. After that is raised, you will attach floor joists and install decking and outside walls.

Make sure to take proper safety precautions including always wearing gloves, goggles and a dust mask when you're cutting or sanding.

### BUILD TIME

**18**  
HRS

### DIFFICULTY




BuildYella.com

# Playset

## WHAT YOU'LL NEED

**YellaWood**  
Pressure Treated Pine

### SUPPLIES




# Playset

## WHAT YOU'LL NEED



### SUPPLIES



# Playset

## WHAT YOU'LL NEED

**YellaWood**  
Pressure Treated Pine

### SUPPLIES

#### WOOD STOCK TOTAL

**6x** 1x4x8'

**8x** 2x4x8'

**5x** 2x4x10'

**1x** 4x4x8'

**10x** 4x4x10'

**15x** 5/4x6x8'

**16x** 5/4x6x10'

YellaWood Protector® Stain & Sealer

### HARDWARE

#### 1 LB BOX

2 1/2" Star-drive decking screws

3 1/2" Star-drive decking screws

1 5/8" Star-drive decking screws

#### 10x

6" FastenMaster TimberLOK

#### 16x

4" FastenMaster TimberLOK

#### 8x

2x4 joist hangers

### TOOLS



Miter saw  
(or hand or  
circular saw)



Table saw



Handsaw




Drill/driver



1/8" Countersink  
drill bit



1/2" Forstner bit



Clamps



Carpenter's  
square



Mallet



Measuring tape



Circular saw



Paint/Stain  
Brush

### BUILD TIME

CUTTING

**4**  
HRS

+

ASSEMBLY

**12**  
HRS

+

FINISHING

**2**  
HRS

=

TOTAL

**18**  
HRS

# Playset

## DIMENSIONS & DIAGRAMS


**YellaWood®**  
Pressure Treated Pine

### Notes:


All measurements are approximate.

**Cut stock in the correct sequence of steps because many dimensions are directly measured** and will vary based on actual stock and construction.

Board dimensions can vary, so be sure to **measure your stock.**




**TOP**



~210"

**RIGHT SIDE**



~95"

~94"

~142"

# Playset

## OVERVIEW OF STEPS

**YellaWood**  
Pressure Treated Pine

### 1: A-FRAME SUPPORTS



### 2: MAIN BEAM



### 3: LADDERS



### 4: FLOOR JOISTS



### 5: CROW'S NEST JOISTS



### 6: CROW'S NEST CLADDING



### 7: DECKING




### 8: REAR CLADDING



### 9: FINISHING




### 10: ACCESSORIES




### CUTLIST & DIAGRAMS FOR JIGS USED


#### A-FRAME MARKING JIG



#### A-FRAME TOP BEAM SPACER JIG



#### A-FRAME SIDE CLADDING SPACER JIG



**Note:** Why are these jigs necessary? To provide accuracy and consistency between parts and make cutting and assembly easier. Using jigs will result in a playset that is safer, stronger, and better looking. Watch the video to see how to make these jigs.









# Playset


## DIMENSIONS & DIAGRAMS

### 1<sup>ST</sup> SECTION: THE TWO OUTSIDE SUPPORTS



### ASSEMBLY VIEW OUTSIDE SUPPORTS

Make this assembly twice.  
Outside supports are identical.





# Playset


## DIMENSIONS & DIAGRAMS

**YellaWood®**  
Pressure Treated Pine

### 3<sup>RD</sup> SECTION: INSIDE RIGHT SUPPORT



### ASSEMBLY VIEW INSIDE RIGHT SUPPORT




















# Playset


## DIMENSIONS & DIAGRAMS

**YellaWood**  
Pressure Treated Pine

### ASSEMBLY VIEW MAIN BEAM



### FRONT



### BACK















### STEP 3: LADDERS

**A:** Attach to Structure

**A1**



Position and install the bottom rung, part (X). Attach using 2 1/2" screws at the end of each board.

**A2**



Using the 3 3/4" spacer jig from before, continue to install parts (X) up the A-frame. The top edge of the top rung should be slightly below the top edge of part (G).

**A3**



Repeat this process for the ladder at the back of the inside A-frames.

**A4**



Finally, install part (W) on the front of the crow's nest using 3 1/2" screws.

# Playset



## DIMENSIONS & DIAGRAMS

**YellaWood**  
Pressure Treated Pine

### STEP 4: FLOOR JOISTS



### CUTLIST




# Playset


## DIMENSIONS & DIAGRAMS

**YellaWood**  
Pressure Treated Pine

### ASSEMBLY VIEW FLOOR JOISTS



### TOP



### BOTTOM



# Playset





## DIMENSIONS & DIAGRAMS

**YellaWood**  
Pressure Treated Pine

### STEP 5: CROW'S NEST JOISTS



### CUT LIST











# Playset









## DIMENSIONS & DIAGRAMS

**YellaWood**  
Pressure Treated Pine

### STEP 6: CROW'S NEST CLADDING



### CUTLIST




# Playset


## DIMENSIONS & DIAGRAMS

**YellaWood**  
Pressure Treated Pine

### ASSEMBLY VIEW CROW'S NEST CLADDING




### FRONT



### LEFT SIDE

**ASSEMBLY VIEW  
CROW'S NEST CLADDING**



### STEP 6: CROW'S NEST CLADDING

**A:** Install Blocking Supports

**A1**



Install parts (LL) along the back of part (P). The top edge of part (LL) should be flush with the top edge of part (P). Attach using 2 ½" screws from the outside.

**A2**



Repeat on the other side of the crow's nest, this time making sure the top edge of part (LL) is flush with the top edge of part (K). This will provide support for the decking to come.

**A3**



Next, install parts (KK) vertically, using part (AA) to help position them. Part (KK) should butt up against part (AA) at the bottom, and butt up against part (LL) at the top. Attach using 1 ⅝" screws from the outside.

**A4**



Attach parts (JJ) to the inside of parts (R). The top edge of part (JJ) should be flush with the top edge of part (LL). Attach with 2 ½" screws from the inside.



### STEP 6: CROW'S NEST CLADDING

**B:** Attach to Structure

**B1**



Attach the lowermost part (EE) to the front of the crow's nest using 2 ½" screws. Align part (EE) with parts (L) and (Q).

**B2**



Next, attach part (FF) at the top of the crow's nest using 3 ½" screws. Align part (FF) with parts (H). Then, install the remaining parts (EE) on the front of the crow's nest, from bottom to top.

**B3**



The remaining parts (II), (GG), and (HH) should fit into the remaining gaps on the crow's nest.

**B4**



For parts (II) and (HH), the screws should be at the ends of the board and go into the blocking part (KK).

**B5**




Be sure to pre-drill and countersink when screwing this close to the ends of the boards.

# Playset






## DIMENSIONS & DIAGRAMS

**YellaWood**  
Pressure Treated Pine

### STEP 7: DECKING




### CUTLIST




# Playset

## DIMENSIONS & DIAGRAMS

### ASSEMBLY VIEW DECKING



### TOP



### BOTTOM

### STEP 7: DECKING

**A:** Attach to Joists

**A1**



Position the first decking board (MM) against the posts of the A-frame at the front of the structure.

**A2**



Center and attach using 2 1/2" screws. Use 2 screws at each floor joist location, for a total of 8 screws per board (MM). Set out the remaining (MM) boards but do not screw them in.

**A3**



The final board of this decking will be board (NN) which should fit up against the rear posts of the A-frames. Now you can attach all these boards with 2 1/2" screws into the joists below.

**A4**



Install parts (OO) at the three openings of the structures. They should project slightly beyond the A-frames.

**A5**



Position and install parts (PP) and (QQ) as the decking for the crow's nest. Part (QQ) will sit between the posts (R). Attach using 2 1/2" screws into the blocking you installed below.

# Playset



## DIMENSIONS & DIAGRAMS

**YellaWood**  
Pressure Treated Pine

### STEP 8: REAR CLADDING




### CUTLIST




# Playset

## DIMENSIONS & DIAGRAMS

### ASSEMBLY VIEW REAR CLADDING



### TOP



### BACK



### STEP 8: REAR CLADDING

**A:** Attach to Structure

**A1**



Position part (RR) on the back of the A-frame posts. Making sure the outer edge is flush with the 4x4 posts behind it, attach part (RR) with 2 ½" screws.

**A2**



Alternate boards (SS) and (RR) up the structure, keeping the outside edges flush with the 4x4 posts behind them.

**A3**



Attach all of the parts (RR) and (SS) with 2 ½" screws into the 4x4 posts behind them.

# Playset

## DIMENSIONS & DIAGRAMS

**YellaWood®**  
Pressure Treated Pine

### STEP 9: FINISHING



YellaWood® brand products provide the best available pressure treated lumber protection against rot, fungal decay and termites. Sanding edges is recommended to reduce snags and splintering. At a minimum, we recommend annual application of a water repellent. You can also paint or stain it if you prefer.

#### A1



Ease any sharp edges with a medium grit sandpaper. Apply a finish to the wood if desired.

#### A2




We recommend long lasting YellaWood Protector® semi-transparent stain and water repellent wood sealer, the only stain backed by the famous Yella Tag. Follow manufacturer's recommendations for application.

# Playset

## DIMENSIONS & DIAGRAMS

**YellaWood**  
Pressure Treated Pine

### STEP 10: ACCESSORIES



Choose your own playset accessories based on your needs. One or both of the standard swings shown can be replaced by toddler or glider swings if needed.

A1




Make a mark on beam (T) 26" from the left edge of beam (T). Make a second mark 18" further in. Drill holes at these points to hold your swing hanger bolts. Follow the swing hanger bolt manufacturer's instructions for this step.

A2



Repeat this step on the right side of beam (T). After installing the swing hanger bolts, follow the swing manufacturer's instructions for how to attach the swings.

A3



Attach the slide to the decking. Follow the slide manufacturer's instructions for this step. Use approved hardware to attach the slide and swings.

**CONGRATULATIONS ON COMPLETING YOUR VERY OWN OUTDOOR PLAYSET! TIME TO LET YOUR KIDS ENJOY IT. NEVER LET CHILDREN USE THE PLAYSET WITHOUT PROPER SUPERVISION.**



# Playset

GALLERY

**YellaWood**  
Pressure Treated Pine



### FOR INTERIOR OR EXTERIOR APPLICATIONS

Use fasteners and hardware that are in compliance with the manufacturer's recommendations and the building codes for their intended use. As with any good design and construction practices, treated wood should not be used in applications where trapped moisture or water can occur. Where design and/or actual conditions allow for constant, repetitive or long periods of wet conditions, only stainless steel fasteners should be used.

### FOR EXTERIOR APPLICATIONS

The following minimum galvanization levels may be used for connectors, joist hangers, fasteners and other hardware that are placed in direct contact with exterior applications of micronized copper treated wood:

- **Fasteners** – nails, screws, etc.      ASTM – A 153 (1 oz/ft<sup>2</sup>)
- **Hardware** – connectors, joist hangers, etc.      ASTM – A 653 G90 (0.90 oz/ft<sup>2</sup>)

The effects of other building materials within a given assembly, along with environmental factors, should also be considered when selecting the appropriate hardware and fasteners to use for a given project containing treated wood.

Stainless Steel fasteners and hardware are required for Permanent Wood Foundations below grade and are recommended for use with treated wood in other severe exterior applications such as swimming pools, salt water exposure, etc. Type 304 and 316 are recommended grades to use.

### ALUMINUM

Aluminum building products may be placed in direct contact with YellaWood® brand products used for interior uses and above ground exterior applications such as decks, fencing, and landscaping projects. Examples of aluminum products include siding, roofing, gutters, door and window trim, flashing, nails, fasteners and other hardware connectors. However, direct contact of treated products and aluminum building products should be limited to code-compliant construction applications that provide proper water drainage and do not allow the wood to be exposed to standing water or water immersion.

We recommend you contact the aluminum building products manufacturer for its recommendations regarding use of its aluminum products in contact with treated wood in ground contact applications or when exposed to salt water, brackish water, or chlorinated water, such as swimming pools or hot tubs.

Also check with the aluminum building products manufacturer regarding compatibility with other chemicals and cleaning agents and the use of their aluminum products in commercial, industrial, and specialty applications such as boat construction.

YellaWood® brand pressure treated products are treated with preservatives (the "Preservatives") and preservative methods and technologies of unrelated third parties. For details regarding the Preservatives, methods, and technologies used by Great Southern Wood Preserving, Incorporated, see [www.yellowood.com/preservative](http://www.yellowood.com/preservative) or write us at P.O. Box 610, Abbeville, AL 36310. Ask dealer for warranty details. For warranty or for important handling and other information concerning our products including the appropriate Safety Data Sheet (SDS), please visit us at [www.yellowood.com/warranties](http://www.yellowood.com/warranties) or write us at P.O. Box 610, Abbeville, AL 36310. YellaWood®, YellaWood Protector® and the yellow tag are federally registered trademarks of Great Southern Wood Preserving, Incorporated.

Great Southern Wood Preserving, Incorporated makes no warranties expressed or implied as to the fitness for a particular purpose of this plan.

- Consult the end tag to determine which preservative or preservative system was used in the treatment of that particular product. YellaWood® brand products may be used in direct contact with aluminum building products when limited to code-compliant construction applications that provide proper water drainage and do not allow the wood to be exposed to standing water or water immersion.
- Use fasteners and other hardware that are in compliance with building codes for the intended use.
- Do not burn preserved wood.
- Wear a dust mask and goggles when cutting or sanding wood.
- Wear gloves when working with wood.
- Some preservative may migrate from the treated wood into soil/water or may dislodge from the treated wood surface upon contact with skin.
- Wash exposed skin areas thoroughly.
- All sawdust and construction debris should be cleaned up and disposed of after construction.
- Wash work clothes separately from other household clothing before reuse.
- Preserved wood should not be used where it may come into direct or indirect contact with drinking water, except for uses involving incidental contact such as fresh water docks and bridges.
- Do not use preserved wood under circumstances when the preservative may become a component of food, animal feed or beehives.
- Do not use preserved wood as mulch.
- Only preserved wood that is visibly clean and free of surface residue should be used. If the wood is to be used in an interior application and becomes wet during construction, it should be allowed to dry before being covered or enclosed.
- Mold growth can and does occur on the surface of many products, including untreated and treated wood, during prolonged surface exposure to excessive moisture conditions. To remove mold from the treated wood surface, wood should be allowed to dry. Typically, mild soap and water can be used to remove remaining surface mold. For more information visit [www.epa.gov](http://www.epa.gov).
- Projects should be designed and installed in accordance with federal, state and local building codes and ordinances governing construction in your area, and in accordance with the National Design Specifications (NDS) and the Wood Handbook.

### **DISPOSAL RECOMMENDATIONS**

Preserved wood may be disposed of in landfills or burned in commercial or industrial incinerators or boilers in accordance with federal, state and local regulations.